

CCT DIMMING



Brightness Adjustable LED Panel Lights

Change the lighting mode according to your mood.



SPECIFICATION



Technical Specification

Features & Benefits:

- 0-10V dimmable and 2.4G Wireless & CCT dimmable LED Flat Panel
- CCT adjustable from 3000K-3500K-4000K-5000K
- No additional wire connections
- UL/cUL DLC 4.2 with isolated external power supply
- LED Source: SMD2835 0.5W. CRI>80
- PMMA LGP
- 5 years warranty

Input Voltage: AC100V~277V 50Hz~60Hz

THD: ≤ 15 %

PF: >0.95 Non-flicker

Power Efficiency: >90 %

Beam Angle: 120°


Material: AL+PMMA+PS

Working Temperature: -20℃~+45℃

Storage Temperature: -25℃~+65℃

IP Grade:IP40

Working Life-span: 50,000H




Specifications


| Model | Watt | Input Voltage | Lumens | LEDs | Size | CCT | N.W |
|----------------------|------|---------------|--------------|----------|----------|-------------|-----------|
| TLR-36W-66-28-TG-02 | 36W | AC 100-277V | 110-120 lm/W | SMD 2835 | 2 * 2 ft | 3000K-5000K | 3.7 kg/pc |
| TLR-40W-66-28-TG-02 | 40W | | | | | | |
| TLR-45W-66-28-TG-02 | 45W | | | | | | |
| TLR-40W-123-28-TG-02 | 40W | | | | 1 * 4 ft | | 3.8 kg/pc |
| TLR-45W-123-28-TG-02 | 45W | | | | | | |
| TLR-50W-126-28-TG-05 | 50W | | | | 2 * 4 ft | | 7.2 kg/pc |
| TLR-60W-126-28-TG-05 | 60W | | | | | | |
| TLR-72W-126-28-TG-05 | 72W | | | | | | |



2 * 2 ft



1 * 4 ft



2 * 4 ft

CCT ADJUSTABLE



3000K



5000K




3000K

3500K

4000K

5000K



CCT can be adjusted between 3000K-5000K as you wish .

BRIGHTNESS ADJUSTABLE



Brightness Dimming:

- ① Step Dimming
- ② Continuous Dimming



REMOTE CONTROL



HANDHELD REMOTE CONTROL

| | | | |
|--|----------------------------------|---|--|
| <input type="radio"/> ON <input type="radio"/> OFF | <input type="radio"/> ON Turn on | <input type="radio"/> OFF Turn off | <input type="radio"/> ⌚ Delayed turn off |
| <input type="checkbox"/> 5000K | <input type="checkbox"/> 3500K | <input type="checkbox"/> 🌟 25% brightness | <input type="checkbox"/> 🌟 75% brightness |
| <input type="checkbox"/> 4000K | <input type="checkbox"/> 3000K | <input type="checkbox"/> 🌟 50% brightness | <input type="checkbox"/> 🌟 100% brightness |
| ▲ Increase brightness | ▼ Decrease brightness | ⬅️ Decrease color temperature | ➡️ Increase color temperature |

WALL SWITCH




| | |
|--|---|
| | Turn on |
| | Turn off |
| | Brightness adjustment |
| | Press CCT button to adjust the temperature, 3000K/3500K/4000K/5000K |

PACKAGE




| Item | N.W. | Carton Size(mm) | Qty | G.W. | Quantity loaded by 20 GP container | Quantity loaded by 40 GP container | Quantity loaded by 40 HQ container |
|----------|----------|-----------------|----------|------------|------------------------------------|------------------------------------|------------------------------------|
| 2 x 2 FT | 3.7kg/pc | 650x645x170 | 4pcs/CTN | 16.8kg/CTN | 1620 | 3200 | 3700 |
| 2 x 4 FT | 7.2kg/pc | 1255x645x85 | 2pcs/CTN | 16.4kg/CTN | 840 | 1630 | 1900 |
| 1 x 4 FT | 3.8kg/pc | 1250x345x170 | 4pcs/CTN | 17.2kg/CTN | 1428 | 3000 | 3300 |




INSTALLATION




Ceiling recessing




1.Remove ceiling plaster slab



2. Connect power supply



3. Fix the panel light into right place



4.Stabilize the panel

Suspending



1. A. Fix the anchor into target place on the ceiling.
B. Fix the installation mount on the ceiling with plastic anchor.




2. Hang the panel to ceiling suspending installation kits



3. Adjust the length of steel wire. Connect the power supply


surface mounted



1. take both profile A and B from accessory pack.




2. Assembling 3 pieces aluminum profile together with screw.



3. Fix semi-finished frame onto ceiling with screw (Plastic anchor for concrete ceiling only).



4. Slide panel into frame properly.



5. Fix the last piece of aluminum profile with screw after panel is well placed.

CONTACT US



Tel : (845) 300-9399



E-mail : billn@rocklandled.com



Web : www.rocklandled.com



Address : 201 Main St Nyack New York 10960